

US005719107A

United States Patent [19]

Outten et al.

[11] Patent Number:

5,719,107

[45] Date of Patent:

Feb. 17, 1998

[54] CRANKCASE LUBRICANT FOR HEAVY DUTY DIESEL OIL

[75] Inventors: Edward Francis Outten, Beast Brunswick; Andrew James Dakiel Ritchie, Chatham, both of NJ.

[73] Assignce: Exxon Chemical Patents Inc. Linden, N.J.

[21] Appl. No.: 695,353

[22] Filed: Ang. 9, 1996

[56]

References Cited

U.S. PATENT DOCUMENTS

4,282,107	8/1981	Zoleshi et el 252/42.7
4,904,401		Ripple et al 252/32.7 E
4,938,880		Waddoups et al 252/32.7 E
4,938,883		Slatna 252/39
4,941,984		Chambetlin et al 252/39
4,957,649		Ripple et al 252/32.7 B
4,981,602		Rippic et al
5,102,566	4/1992	Fetterman et al 252/32.7 E
5,141,657	8/1992	Fetterman et al 252/32.7 E
5,202,036	4/1993	Ripple et al
5,312,554	5/1994	Waddoups et al 508/507
5,320,765	6/1994	Fetterman et al 252/32.7 E
5,451,333	9/1995-	Waddoups et al 508/539
5,486,300		Salomon
5,498,355	3/1996	Perozzi 508/454
5,558,802	9/1996	Dowling 508/518
		-

FOREIGN PATENT DOCUMENTS

0 277 729 A1 8/1988 European Pat. Off. C10M 163/00

0 317 354 5/1989 European Pat. Off. . WO 92/18588 10/1992 WIPO .

OTHER PUBLICATIONS

PCT Search Report date Sep. 5, 1995.

Mack Truck Technical Services Standard Test Procedure No. 5GT 57 "Mack T-7: Diesel Engine Oil Viscosity Evaluation", Aug. 31, 1984 (Mack T-7).

Mack Truck Technical Services Standard Test Procedure No. 5GT 76 "Mack T-8: Diesel Engine Oil Viscosity Evaluation", Oct. 1993 (Mack T-8).

"Corrosion in Lubricant Systems", Dr. Tony Smith, M.Sc., Anti-Corrosion, Nov. 1983, pp. 15-16.

"Courosion of Copper and Lead Containing Materials by Diesel Lubricants", C. M. Cusano and I. C. Wang, Curamins Engine Company, Journal of the Society of Tribologists and Inheication Engineers, Lubrication Engineering, vol. 51, 1, pp. 89-95 Date unavailable.

"The Function of Lube-Oil in Fighting Corrosion in Medium-Speed Engines", P. R. Belcher, Bsc, CEng, Shell International Petroleum Co. Ltd., Lubrication Engineering, Feb. 1993, pp. 145-150.

"Protective Automotive Lubricants", András Zekar, Hungarian Hydrocarbon Institute, Journal of the Society of Tribologists and Lubrication Engineers, vol. 49, 2, pp. 145–150 date unavailable.

Primary Examiner Jacquetine V. Howard Attorney, Agent, or Firm E. C. Bakun

[57]

ABSTRACT

Thus, the instant invention is directed toward an oil for diesel engines comprising an admixture of (A) a major amount of an oil of libricating viscosity, (B) at least 4 mass % dispersant, (C) at least 0.3 mass % of a metal phenate, (D) less than 0.1 mass. % friction modifier, (E) less than 0.3 mass % of ashless sulfurized phenois and, (F) less than 0.12 mass % neutral calcium sulfonate.

14 Claims, No Drawings